

BS-533A

SPEAKER

5" 6W WALL-MOUNTED SPEAKER



BS-533A
5" 6W 100V LINE WITH ALUMINIUM GRILLE

BS-533A is a wall-mounted speaker crafted from durable ABS resin and features an aluminum grille. It offers versatile installation options, allowing it to be hooked or mounted directly onto the wall. The screw-type input terminal simplifies cable connections, reducing the risk of loose wires and potential short circuits, while also supporting bridge wiring. Changing the input impedance is straightforward by following the provided instructions and connecting the appropriate color-coded wire. This speaker is powered by a 5-inch dual-cone driver, with tapping wattage details available in the technical specifications below.



Technical Specifications

BS-533A	
Power Handling Capacity	6W 100V
Rated Impedance	8 Ohm
Speaker Type	Dual Cone
Speaker Size (Diameter)	5"
Sensitivity	92dB (1W,1m)
Frequency Response	130-15 KHz
Transformer Taping (100 V Line) @ 8 Ohm	6W/3W/1.5W 8 Ohm
Primary Impedance of Tapping (Ohm)	10K/3.3K/1.6K
Grille/Enclosure	Aluminium / ABS
Overall Size	312MM (H) x 210MM (W) x 85MM (D)
Weight	1.4 KG
Colour	White

