

SL6-060

SPEAKER (IP 44)

COMMERCIAL-GRADE PUBLIC ADDRESS COLUMN SPEAKER



**SL6-060 | Commercial-Grade Public Address Column Speaker with IP44 Weather Resistance**

The **SL6-060** is a high-efficiency, 100V line public address column speaker engineered for clear, intelligible audio distribution in demanding **indoor and outdoor** environments. Combining the durability of a full-aluminum enclosure with IP44-rated weather resistance, it is purpose-built for installations requiring reliable, energy-efficient sound reinforcement across expansive or multi-zone spaces.

**Optimized for PA Applications:** Designed specifically for voice reproduction and background music in distributed audio systems, delivering exceptional speech clarity and tonal balance ideal for worship spaces, lecture halls, hotels, and public venues.

**Efficient Power Utilization:** Operates at a 60W draw on a 100V line while achieving output performance comparable to conventional 120W systems, reducing energy costs without sacrificing coverage or intelligibility.

**All-Aluminum Architecture:** Lightweight yet rugged corrosion-resistant construction ensures longevity in humid, outdoor, or temperature-variable environments.

**Directional Flexibility:** Integrated adjustable mounting bracket allows precise angling to target sound projection, optimizing coverage for seated audiences or open areas.

**Proven Deployment Success:** Trusted in large-scale installations including mosques, hospitality venues, and conference facilities, praised for its consistent performance and low-maintenance design.

SL6-060

IP44 WEATHER RESISTANCE FULL ALUMINIUM

BODY COLUMN SPEAKER

Technical Specifications

| SL6-060                                    |                                                              |
|--------------------------------------------|--------------------------------------------------------------|
| Power Handling Capacity                    | 60W 100V LINE                                                |
| Rated Impedance                            | 8 Ohm                                                        |
| Speaker Type                               | 1 x 6.5" Vocal-Optimized Driver + 5 x 6.5" Full-Range Driver |
| Sensitivity                                | 98dB (1W,1m)                                                 |
| Frequency Response                         | 100-18KHz                                                    |
| Transformer Taping (100 V Line)<br>@ 8 Ohm | 60W/30W<br>8 Ohm                                             |
| Primary Impedance of Tapping (Ohm)         | 10K/3.3K/1.6K                                                |
| Grille /Enclosure                          | Full Aluminium                                               |
| Overall Size                               | 1384MM (H) x 227MM (W) x 125MM (D)                           |
| Weight                                     | 12.5 KG                                                      |
| Colour                                     | White                                                        |

