

WM-420 WM-630

SPEAKER

NEODYMIUM 2-WAY WALL MOUNT SPEAKER



[WM-420 \(B/W\)](#)

4" 20W 100V LINE NEODYMIUM WALL MOUNT SPEAKER WITH TAPPING

[WM-630 \(B/W\)](#)

6" 30W 100V LINE NEODYMIUM WALL MOUNT SPEAKER WITH TAPPING



STAINLESS STEEL MOUNTING BRACKET

Exquisite Speaker System: A Symphony of International Engineering

Enjoy rich, immersive sound with your choice of a 1-inch neodymium tweeter paired with either a 4-inch or 6-inch woofer. Whether for balanced everyday listening or deeper bass response, both options deliver exceptional audio with elegant form.

Innovative Neodymium Tweeter

Equipped with a neodymium tweeter, this speaker offers powerful high-frequency clarity in a compact design. The strong, lightweight magnet ensures sharp, detailed treble without added bulk.

A Global Collaboration of Design Excellence

This speaker is the result of global expertise—Italian exterior styling, Russian acoustic design, Chinese material engineering, and Malaysian sound tuning—delivering a refined product that performs as beautifully as it looks.

Versatile Aesthetic Options

Available in black or white finishes, with an optional white grille on the full black model. Designed to stand out with style, yet blend seamlessly into upscale interiors.

Technical Specifications

	WM-420	WM-630
Power Handling Capacity	20W 100V	30W 100V
Speaker Driver Type	Woofer + Tweeter	Woofer + Tweeter
Speaker Driver Size	1"(Neodymium) + 4"	1"(Neodymium) + 6"
Sensitivity	90dB (1W,1m)	92dB (1W,1m)
Frequency Response	50 -20 KHz	50 -22 KHz
Transformer Taping (100 V Line) @ 8 Ohm	20W/10W/5W/2.5W 8 Ohm	30W/15W/7.5W/3.8W 8 Ohm
Primary Impedance Of Tapping (Ohm)	500/1K/2K/4K/8 Ohm	334/667/1334/2632/8 Ohm
Secondary Impedance (Ohm)	8 Ohm	8 Ohm
Grille /Enclosure	ABS/ Alluminium	ABS/ Alluminium
Overall Size	247MM (H) x148MM (W) x152MM (D)	335MM (H) x 222MM (W) x 214MM (D)
Accessories	Wall Mount Bracket	Wall Mount Bracket
Weight	4.0 KG	4.7 KG
Colour	Black , White	Black , White

